1.2系列选型规则/Group 1.2 Ordering Code Rules

B	A	P	1.2B	Q5	D	0.8	G1	L3	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other

材质 Material

A	前、后盖材料为铝合金 Front and end cover material aluminum
H	前、后盖材料为铸铁，压力比铝盖高 30bar。Front and end cover material cast iron, pressure 30 bar higher than aluminum covers

功能 Function

P	泵 Pump

系列 Group

1.2	1.2系列 Group1.2
1.2B	1.2B系列 Group1.2B
1.2E	1.2E系列 Group1.2E

旋向 Rotation

D	顺时针转 Clockwise
S	逆时针转 Counter clockwise
R	可正反转 Reversible

排量 Displacement

0.8
1.2
1.7
2.5
3.2
4.3
5
6
6.5
7.8
8.5
10
12

特殊设计 special designing

可选项 Options

	省略-温度范围在-10℃~+80℃,进油口最高绝对压力为3bar。Omit-Range between −10℃ and +80℃,inlet pressure up to max. 3 bar absolute.
V	适用于高温介质，温度范围在-10℃~+120℃。Version suitable for fluid at hi-temperatures, range between −10℃ and +120℃.
H	适用于低温介质，温度范围在-40℃~+80℃。Version suitable for fluid at low-temperatures, range between −40℃ and +80℃.
N	适用于进油口最大绝对压力3~10bar。Version suitable for inlet pressure up to max. 3 and 10 bar absolute.

如需其它特殊选项请联系本公司工程师 For other special options, please contact our engineers.

前盖 Front cover

1.2系列/Group 1.2

Q0	方形前盖（止口φ32） Square front cover (centering φ32mm)
Q2	方形前盖（止口φ32） Square front cover (centering φ32mm)

详见 44 页 See page 44 for details

1.2B系列/Group 1.2B

Q5	方形前盖（止口φ45.2） Square front cover (centering φ45.2mm)

轴伸 Shaft

1.2系列/Group 1.2

G0	扁平轴 Tang shaft
G4	扁平轴 Tang shaft

详见 44 页 See page 44 for details

1.2B系列/Group 1.2B

G1	扁平轴 Tang shaft
G8	扁平轴 Tang shaft

泵体油口 Ports

Z_	公制螺纹（M） Metric thread
L_	英制管螺纹(G) Gas thread
U_	美制管螺纹(UNF-2B) UNF thread
R_	英制锥螺纹(PT) PT thread
X	泵体无油口 Body without ports

特殊结构 Special structure

1.2B系列/Group 1.2B

	省略-默认普通 omit-regular

1.2系列/Group 1.2

	省略-默认普通 omit-regular
_J_	后盖带进油口 Back cover with inlet
Q_	后盖带泄油口 Back cover with oil drain