2系列选型规则/Group 2 Ordering Code Rules

B	A	P	2	B0	D	3	T0	E0	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other

材质 Material

- A — 前、后盖材料为铝合金 Front and end cover material aluminum
- H — 前、后盖材料为铸铁，压力比铝盖高 30bar。Front and end cover material cast iron, pressure 30 bar higher than aluminum covers

功能 Function

- P — 泵 Pump
- M — 马达 Motor

系列 Group

- 2 — 2系列 Group 2
- 2Y — 2Y系列 Group 2Y

旋向 Rotation

- D — 顺时针转 Clockwise
- S — 逆时针转 Counter clockwise
- R — 可正反转 Reversible

排量 Displacement

3 / 4 / 6 / 8 / 10 / 12 / 14 / 16 / 18 / 20 / 22 / 25 / 28 / 30

其他 Other

特殊设计 special designing

可选项 Options

	省略-温度范围在-10℃~+80℃，进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃,inlet pressure up to max. 3 bar absolute.
V	适用于高温介质，温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃.
H	适用于低温介质，温度范围在-40℃~+80℃。 Version suitable for fluid at low-temperatures, range between -40℃ and +80℃.
N	适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute.

如需其它特殊选项请联系本公司工程师
For other special options, please contact our engineers.

前盖 Front cover

- A0 — 菱形前盖(止口φ82.55) Diamond front cover (centering φ82.55mm)
- B0 — 方形前盖（止口φ36.5） Square front cover (centering φ36.5mm)
- B1 — 方形前盖（止口φ38） Square front cover (centering φ38mm)
- B2 — 方形前盖（止口φ80） Square front cover (centering φ80mm)
- Q0 — 方形前盖（止口φ50） Square front cover (centering φ50mm)
- Q2 — 方形前盖（止口φ52），O-RING Square front cover (centering φ52mm),O-RING

轴伸 Shaft

- T0 — 锥形键槽轴 1:8 Taper shaft 1:8
- T1 — 锥形键槽轴 1:5 Taper shaft 1:5
- C0 — 平键轴 straight keyed
- G0 — 扁平轴 Tang shaft
- G1 — 扁平轴 Tang shaft
- H0 — 矩形花键轴 Rectangle spline shaft ⌐⌐4-15x11.4x4
- S0 — SAE花键轴 SAE spline shaft DP16/32-30°-9T
- S1 — SAE花键轴 SAE spline shaft DP16/32-30°-11T
- S8 — SAE花键轴 SAE spline shaft DP16/32-30°-10T

泵体油口 Ports

- E_ — 矩形法兰 Rectangular flange
- F_ — 矩形法兰 Rectangular flange
- F_ — 矩形法兰 Split flange
- Z_ — 公制螺纹（M） Metric thread
- L_ — 英制管螺纹(G) Gas thread
- U_ — 美制管螺纹(UNF-2B) UNF thread
- R_ — 英制锥螺纹(PT) PT thread
- N_ — 美制锥螺纹(NPT) NPT thread
- X — 泵体无油口 Body without ports

特殊结构 Special structure

- 省略-默认普通 omit-regular
- Q_ — 后盖带泄油口 Back cover with oil drain
- __ — 后盖带进出油口 Back cover with inlet and outlet
- DF0 — 后盖带单向阀 Back cover with one-way valve
- YF0 — 后盖带溢流阀 Back cover with relief valve
- HFA_ — 后盖带恒流阀阀 Back cover with constant flow valve